



## Overview

The Pinnacle™ Narrow Sash Sliding Window is an economical sliding window solution compatible with the Emporia™ 100mm centre-glazed commercial framing system. It is an ideal solution for community facilities, commercial and industrial buildings. This window also has excellent water rating characteristics.

## Features

- Suitable for use in public buildings, schools and various industrial applications
- Accepts glass thickness from 4mm – 6.38mm single glazing and 14mm double glazing
- The window is available in double slide configurations
- Direct fixing can be done by using unique “plant-on” head, sill and jamb receiver at timber, steel or aluminium openings
- The double sliding feature makes this product ideal for commercial applications allowing for cleaning of external faces from inside the building
- Choice of locks are keyed and non-keyed cam mechanisms securely fixed to the jamb
- Master key option is available
- The sill is designed to be self-draining
- Water rating of 150Pa\*
- Integrates with Emporia™ commercial framing
- As with all of Lidco’s Emporia™ commercial framing systems there is a range of subsill and subhead options to facilitate on-site installation



Maximum Panel Height <sup>†</sup>	1800mm
Maximum Panel Width <sup>†</sup>	1200mm
Maximum Glass Thickness	≤14mm IGU

<sup>†</sup>Dependant on wind loadings, refer to Lidco limitation tables



\*Standard sill used (testing pending)



## How to Specify

- Aluminium frames to be manufactured using Lidco 740 System: Pinnacle™ Narrow Sash Sliding Window
- Selected framing to be engineered, manufactured and installed in accordance with:  
AS 2047-2048 (Windows in Buildings), AS/NZS 1170 (Loading Code), AS/NZS 1664 (Aluminium Structures Code)
- Selected glazing to be in line with performance requirements as set out in AS 1288 (Glass in Buildings)
- Size limitations are governed by design intent, glass selection and local wind load and deflection requirements

## AutoSpec Specification

All Lidco residential and commercial window and door systems are available in AutoSpec, the intelligent web-based specification engine. AutoSpec allows the Specifier to select the Lidco systems that meets their needs, specify them accurately and then complete the project specification text automatically.



[www.autospec.com.au](http://www.autospec.com.au)




For any specification assistance please call to speak to one of our friendly and knowledgeable technical sales team on 1300 663 848 or email [techsupport@lidco.com.au](mailto:techsupport@lidco.com.au)



740 System Specifier Guide, CAD, PDF files and more are available at [www.lidco.com.au](http://www.lidco.com.au)

## Typical Configurations



Lidco Corporation Pty Ltd  
T 1300 663 848  
[techsupport@lidco.com.au](mailto:techsupport@lidco.com.au)  
[www.lidco.com.au](http://www.lidco.com.au)

Founded in Australia over 65 years ago Lidco is a leading designer and supplier of contemporary and high performance residential and commercial aluminium window and door systems