

Lifestyle™ Sliding Window – 112 System

Lifestyle™ Sliding Windows are ideally suited for residential housing and low rise residential units.

The system allows insect and safety screens to be installed from inside the building, offering extra security and convenience for cleaning. The system uses the latest in window drainage design and incorporates durable sash seals to protect your home from dust and moisture.

The system is engineered to be manufactured in various framing combinations including fixed slide, slide fixed slide and centre bi-part options.




Water Test
Std Sill (Pa)
200

Single Glazed	Cooling	Heating	*Uw	*SHGC
4mm Clear	12%	18%	6.4	0.73
5mm Clear	13%	18%	6.4	0.72
5mm EverGreen	33%	8%	6.4	0.50
6mm Clear	14%	18%	6.4	0.71
6mm Energy Advantage	33%	37%	4.6	0.61
6.38mm Laminate	15%	18%	6.3	0.70
6.38mm ComfortPlus Neutral	46%	29%	4.6	0.45

*Notes: **Uw** is the whole window U-value
SHGC is the whole window solar heat gain coefficient

Recommended Total Window Size[†]

Height: 1500mm
Width: 1000mm

[†]Dependant on wind loadings, refer to Lidco limitation tables

 <p>This manufacturer certifies that this product was designed to conform with AS2047. The design performance has been verified by a NATA accredited test laboratory. This manufacturer is a member of the AWA Accreditation Program.</p>	 <p>ACCREDITED MEMBER</p>	<p>DESIGN PERFORMANCE</p> <p>N4 1500 Pa Structural</p> <hr/> <p>200 Pa Water Resistance</p>	<p>ENERGY RATED</p> 
---	---	---	---